

Guidelines for application of Vinyl DOOR SIGNS

Recommended materials required: Clean soft cloth or duster and your Door Sign.

APPLICATION

(DRY METHOD FOR APPLICATION TO CLEAN DRY SURFACES ON THE VEHICLE)

Generic Instructions

Designated position of door signs:

Make sure your vinyl self adhesive door sign is positioned as specified by your Local Authority Licensing Department.

These signs must be attached directly to the vehicle and only in accordance with these Guidelines.



First choose the correct area on the front door, see left, by offering the door sign up to the designated central position on the front doors. Now thoroughly clean the surface where the sign is to be applied with a clean, dry cloth or duster.



Wipe clean with damp cloth

Peel off about small segment of the backing paper from one end of the door sign, see picture right, and fold over to expose a portion of adhesive on the rear of the printed door sign. Now you have formed a 'hinge'.



Make a flap with backing paper

Apply the exposed portion of the adhesive area on the rear of the sign directly to the door, making sure that the sign is horizontal. Now slowly from the 'hinged' area which is now attached to the vehicle, pull off the remainder of the backing paper and smooth down firmly and evenly with a soft cloth.

n.b. Take care to expel all the air as you go by applying pressure from the centre of the sign.



Slowly pull down backing sheet and smooth down from hinge.

Finally smooth over sign with soft cloth applying pressure. Any small air bubbles may be pricked with a pin and the air expelled by applying pressure.

Please note that these industry standard vinyl materials will take a number of hours to achieve maximum adhesion to the surface of the vehicle.



Smooth whole sign with soft cloth to complete application

CARE AND MAINTENANCE OF DOOR SIGNS

Normal car washing with non-aggressive detergents will keep door signs in prime condition. Wax based products such as 'Turtle Wax' may also be used.

DO NOT USE aggressive or solvent based products such as T-CUT or AutoGlym paint restorers as these products are designed to remove the top layer of paint.

REMOVAL OF DOOR SIGNS

Ensuring that the sign remains in one piece gently peel off from the outside edge and keeping door sign taut pull away from vehicle. Following removal of the sign, clean off any adhesive residue remaining on the vehicle with soapy water. Finally wipe down the surface again with a clean, soft cloth leaving paintwork clean and dry. Applying gentle heat with a hairdryer may be helpful if required.

Disclaimer: the supplier NewAuto Limited trading as Mogo UK (and any associated company) has no control over how signs are cared for, altered, stored, affixed and/or used, or over the surface to which they are applied. As a result, NewAuto Limited trading as Mogo UK (and any associated company) accepts no liability whatsoever, in any circumstances, for any claim or claims for alleged loss or damage relating to the use of, application or removal of the signs supplied. NewAuto Limited is unable to enter any dialogue with the 'trade' on this subject. The purchaser and/or user will be deemed to accept this disclaimer in the use of these products.