



NOTE:

1. All recycled material is subject to the requirements in NYC' s 2025 Specification for Housing and Industrial Estate Roads and Private Street Works - Appendix H
2. See Section 7-05 of NYC' s 2025 Specification for Housing and Industrial Estate Roads and Private Street Works. Sub base should be minimum 150mm thickness beneath kerb raft on bituminous construction
4. Channels only required when gradients is less than 1:80
5. Hot Rolled Asphalt Surfacing shall be used in the following locations: -
 - All A and B class roads,
 - Ghost island right turning lanes and roundabouts on all classes of roads
 - All Industrial estate roads
 - Residential estate roads with a width of 7.3 m or greater.
 - Residential estate roads with a width of 6.5 m that are to be used as bus routes.
 - Other junctions and locations as requested by the Engineer.

Do Not Scale

REVISIONS	
VERSION	DETAILS
1	REVISED IN ACCORDANCE WITH NYC SPECIFICATION FOR HOUSING AND INDUSTRIAL ESTATE ROADS AND PRIVATE STREET WORKS, APRIL 2025



PROJECT:

STANDARD DETAILS

DATE: SEPTEMBER 2025

DRAWING TITLE:

**A2 - INDUSTRIAL ESTATE ROAD
TYPICAL CROSS SECTION**

SCALE: Not to Scale

Revision I